

**MATERIAL SAFETY DATA SHEET****WOODARMOR EXTERIOR SOLID HIDE ACRYLIC LATEX FINISH EXTERIOR WHITE**

HMIS Health- 1

HMIS Fire- 1

HMIS Reactivity- 0

**1 - CHEMICAL PRODUCT AND COMPANY INFORMATION**

**PRODUCT NAME:** WoodArmor Exterior Solid Hide Acrylic Latex Finish Exterior White  
**PRODUCT CODE:** 020973  
**MANUFACTURER:** Sampson Coatings  
**ADDRESS:** 1900 Ellen Road, Richmond, VA 23230  
**INQUIRY PHONE NUMBER:** 804.359.5070 (all non-emergency)  
**EMERGENCY PHONE NUMBER:** 800.424.9300 (Chemtrec)  
**DATE PREPARED:** 5/5/2009 - this document supercedes all previous material safety data sheets.  
**VERSION:** 4.0

**2 - COMPOSITION / HAZARDOUS INGREDIENTS**

INGREDIENT	CAS NUMBER	WT %
Water	7732-18-5	20 - 40
Titanium Dioxide	13463-67-7	10 - 20
Texanol	25265-77-4	0 - 5
Propylene Glycol	57-55-6	0 - 5
Nepheline Syenite	37244-96-5	10 - 15
pigment	Proprietary	20 - 40
polymer	Proprietary	0 - 20

**3 - HAZARDS****NONFLAMMABLE  
AQUEOUS****EMERGENCY OVERVIEW INSTRUCTIONS**

Combustion fumes may be harmful.  
 May cause skin irritation on prolonged contact.  
 Vapors irritating to eyes and respiratory tract.

**EYE CONTACT:** May cause irritation.

**SKIN CONTACT:INHALATION:** Harmful if inhaled. Repeated overexposure instances or a single large exposure may sensitize an individual. Persons sensitized by a previous exposure will show symptoms when exposed to concentrations much lower than exposure limits or exposure guidelines. Sensitized individuals may show symptoms when exposed to dust, cold air or other irritants. This increased sensitivity may last for weeks, months or it may be permanent. May cause allergic respiratory reaction. Lung damage (including fibrosis and decreased lung function) and respiratory sensitization may be permanent. Symptoms may occur hours after exposure and include nausea, lightheadedness, drowsiness, dizziness, loss of coordination, chest tightness, wheezing, cough, shortness of breath and asthmatic attack.

**INGESTION:CHRONIC HEALTH EFFECTS:** Prolonged overexposure to solvent vapors may cause adverse effects to the liver, urinary, cardiovascular and reproductive systems. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

**SIGNS / SYMPTOMS:** Overexposure may cause headaches and dizziness.

**TARGET ORGANS:** No information found.

**PRE-EXISTING CONDITIONS:** Skin allergies, eczema, asthma and other respiratory disorders may be aggravated by exposure.

**4 - FIRST AID**

EYE CONTACT:	Flush eyes with large amounts of water for 15 minutes. Get medical attention if symptoms of overexposure or irritation persists.
SKIN CONTACT:	Run a gentle stream of water over the affected area for 15 minutes. A mild soap may be used if available.
INHALATION:	Remove from area to fresh air. If symptomatic, contact a poison control center, emergency room or physician for treatment information.
INGESTION:	Gently wipe or rinse the inside of the mouth with water. Never give anything by mouth to an unconscious person. Contact a poison control center, emergency room or physician right away as further treatment may be necessary.

**5 - FIRE FIGHTING MEASURES**

FLASH POINT:	None.
EXTINGUISHING MEDIA:	Dry chemical, Carbon dioxide, Foam, Water spray for large fires
PROTECTIVE EQUIPMENT:	Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and clothing.
SPECIAL FIREFIGHTING PROCEDURES:	None.
UNUSUAL FIRE/EXPLOSION HAZARDS:	None.



NFPA Health- 1

NFPA Fire- 1

NFPA Reactivity- 0

**6 - ACCIDENTAL RELEASE MEASURES**

PERSONNEL PRECAUTIONS:	Use personal protective equipment.
ENVIRONMENTAL PRECAUTIONS:	Avoid runoff into ditches, storm sewers and other waterways.
SPILL CLEANUP MEASURES:	Absorb spill with inert material and place in a chemical waste container. Provide ventilation. Clean up spills immediately and observe precautions related to protective equipment.

**7 - HANDLING AND STORAGE**

HANDLING:	Use with adequate ventilation. Avoid breathing vapor and contact with eyes, skin and clothing.
STORAGE:	Store in a cool dry well ventilated area. Keep away from heat and flame.
HYGIENE:	Wash thoroughly after handling. Avoid contact with eyes and skin. Avoid inhaling vapor or mist.

**8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

ENGINEERING CONTROLS:	The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits. Eye washes and showers for emergency use.
EYE / FACE PROTECTION:	Wear splash goggles on face to protect eyes.
SKIN PROTECTION:	Wear butyl rubber gloves, protective clothing and chemical resistant boots.
RESPIRATORY PROTECTION:	If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers.
OTHER PROTECTIONS:	Facilities that store or utilize this material should be equipped with an eyewash facility and a safety shower.
PEL (OSHA) / TLV (ACGIH):	<p>Titanium Dioxide (13463-67-7)            PEL (OSHA): 15 mg/m3 (TWA)            TLV (ACGIH): 10 mg/m3 (TWA)</p> <p>Texanol (25265-77-4)            PEL (OSHA): 100 ppm (TWA)            TLV (ACGIH): 100 ppm (TWA)</p> <p>Propylene Glycol (57-55-6)            PEL (OSHA): Not Established            TLV (ACGIH): Not Established</p>

Nepheline Syenite (37244-96-5)  
 PEL (OSHA): 5 mg/m<sup>3</sup> TWA (respirable fraction)  
 TLV (ACGIH): 10 mg/m<sup>3</sup> TWA (total dust)

## 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL APPEARANCE: Opaque Liquid  
 COLOR: White  
 FLASH POINT: None.  
 BOILING RANGE: 211 - 213 °F  
 DENSITY: 12.1 - 12.5 lbs/gal  
 MATERIAL VOC (as supplied): 1.1 lbs/gal 134 g/l  
 COATING VOC (EPA Method 24): 1.1 lbs/gal 134 g/l

## 10 - STABILITY AND REACTIVITY

CHEMICAL STABILITY: The risk for chemical reactivity is low to none.  
 HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur.  
 MATERIALS TO AVOID: None.  
 DECOMPOSITION PRODUCTS (FIRE): carbon monoxide; carbon dioxide; aldehydes; formaldehyde; oxides of nitrogen; oxides of phosphorus; acrylic monomers; hydrogen chloride; ketones; crystalline silica; oxides of sulfur; metallic oxides

## 11 - TOXICOLOGICAL INFORMATION

LD<sub>50</sub>, LC<sub>50</sub>: Titanium Dioxide (13463-67-7 )  
 LD50 (oral rat): Not Established  
 LC50 (inhalation rat): Not Established  
 Texanol (25265-77-4 )  
 LD50 (oral rat): 6,517 mg/kg  
 LC50 (inhalation rat): 3.55 mg/l (6 hr)  
 Propylene Glycol (57-55-6 )  
 LD50 (oral rat): 20,000 mg/kg  
 LC50 (inhalation rat): Not Established  
 Nepheline Syenite (37244-96-5 )  
 LD50 (oral rat): Not Established  
 LC50 (inhalation rat): Not Established

## 12 - ECOLOGICAL INFORMATION

No data available.

## 13 - DISPOSAL CONSIDERATIONS

Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Dispose of waste in accordance with Federal, State and Local regulations regarding pollution.

## 14 - TRANSPORT INFORMATION

DOT UN Number: No applicable DOT UN number.  
 DOT Hazard Class: This material is not flammable.  
 DOT Description/Name: This product is non-regulated.

## 15 - REGULATORY INFORMATION

TSCA CERTIFICATION: The chemicals in this material are on the TSCA Section 8 Inventory.  
 SARA 313: This product does not contain any chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.  
 California Proposition 65: This product does not contain any chemicals listed by California as known to cause cancer, birth defects or other reproductive harm in compliance with Proposition 65, the Safe Drinking Water and Toxic Enforcement Act of 1986.

## 16 - OTHER INFORMATION

HMIS Key

- 4 = Severe Hazard
- 3 = Serious Hazard
- 2 = Moderate Hazard
- 1 = Slight Hazard
- 0 = Minimal Hazard

### **Acronyms and Abbreviations**

ACGIH - American Conference of Governmental Industrial Hygiene (<http://www.acgih.org>)

OSHA - U.S. Occupational Health and Safety Administration (<http://www.osha.gov>)

IARC - International Agency for Research on Cancer (<http://www.iarc.fr>)

NTP - National Toxicology Program (<http://ntp.niehs.nih.gov>)

NIOSH - National Institute for Occupational Safety and Health (<http://www.cdc.gov/niosh>)

PEL - Permissible Exposure Limit

TLV - Threshold Limit Value

TWA - Time Weighted Average (over 8 hour period)

STEL - Short Term Exposure Limit

NFPA is a registered trademark of the National Fire Protection Association ([www.nfpa.org](http://www.nfpa.org)).

HMIS is a registered trademark of the National Paint & Coatings Association ([www.paint.org/hmis/](http://www.paint.org/hmis/)).

### **DISCLAIMER**

This document is generated to distribute health, safety and environmental data. It is not a specification sheet nor should any data be construed as a specification. The information on this MSDS was obtained from sources which we believe are reliable. The information is provided without any warranty, expressed or implied, regarding its correctness. Some information and conclusions are drawn from sources other than direct tests on the product.

The methods of handling, storage, use and disposal of the product are beyond our control and for this and other reasons we do not assume responsibility. We expressly disclaim liability for loss, damage, or expense arising out of or in any way connected with the handling, storage, use or disposal of this product.

If the product is used as a component in another product, this MSDS information may not be applicable.