

MATERIAL SAFETY DATA SHEET**WOODARMOR WHITE CONVERSION VARNISH GLOSS**

HMIS Health- 2*

HMIS Fire- 3

HMIS Reactivity- 0

* Chronic Health Hazard

1 - CHEMICAL PRODUCT AND COMPANY INFORMATION

PRODUCT NAME: WoodArmor White Conversion Varnish Gloss
PRODUCT CODE: 235049
MANUFACTURER: Sampson Coatings
ADDRESS: 1900 Ellen Road, Richmond, VA 23230
INQUIRY PHONE NUMBER: 804.359.5070 (all non-emergency)
EMERGENCY PHONE NUMBER: 800.424.9300 (Chemtrec)
DATE PREPARED: 4/27/2011 - this document supercedes all previous material safety data sheets.
VERSION: 4.0

2 - COMPOSITION / HAZARDOUS INGREDIENTS

INGREDIENT	CAS NUMBER	WT %
Xylenes	1330-20-7	5 - 10
Methyl Ethyl Ketone	78-93-3	0 - 5
Butanol	71-36-3	5 - 10
Toluene	108-88-3	15 - 20
Light Aromatic Solvent Naphtha	64742-95-6	< 0.2
Acetone	67-64-1	0 - 5
Isopropanol	67-63-0	5 - 10
Methanol	67-56-1	0 - 5
Isobutyl Acetate	110-19-0	0 - 5
Methyl Isoamyl Ketone	110-12-3	0 - 5
Ethylbenzene	100-41-4	0 - 5
Formaldehyde	50-00-0	< 0.2
Titanium Dioxide	13463-67-7	10 - 20
Diisononyl Phthalate	68515-48-0	0 - 5
polymer	Proprietary	20 - 40

3 - HAZARDS**EMERGENCY OVERVIEW INSTRUCTIONS**

Combustion fumes may be harmful.
 May cause skin irritation on prolonged contact.
 Vapors irritating to eyes and respiratory tract.

EYE CONTACT: May cause eye irritation.
SKIN CONTACT: May cause slight skin irritation. May be absorbed through the skin. Prolonged or repeated contact may cause an allergic skin reaction.
INHALATION: Prolonged or excessive inhalation may cause respiratory tract irritation.
INGESTION: May be harmful if swallowed. May cause vomiting.
CHRONIC HEALTH EFFECTS: Prolonged overexposure to solvent vapors may cause adverse effects to the liver,

SIGNS / SYMPTOMS:	urinary, cardiovascular and reproductive systems. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.
TARGET ORGANS:	Overexposure may cause headaches and dizziness.
PRE-EXISTING CONDITIONS:	No information regarding target organs was found.
	No information regarding pre-existing conditions was found.

4 - FIRST AID

EYE CONTACT:	Flush eyes with large amounts of water for 15 minutes. Get medical attention if symptoms of overexposure or irritation persists.
SKIN CONTACT:	Run a gentle stream of water over the affected area for 15 minutes. A mild soap may be used if available.
INHALATION:	Remove person from area of spill to a location with fresh air.
INGESTION:	Gently wipe or rinse the inside of the mouth with water. Never give anything by mouth to an unconscious person. Contact a poison control center, emergency room or physician right away as further treatment may be necessary.

5 - FIRE FIGHTING MEASURES

FLASH POINT:	-4 °F
EXTINGUISHING MEDIA:	Dry chemical, Carbon dioxide, Foam, Water spray for large fires.
PROTECTIVE EQUIPMENT:	Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and clothing.
SPECIAL FIREFIGHTING PROCEDURES:	None.
UNUSUAL FIRE/EXPLOSION HAZARDS:	None.



NFPA Health- 2

NFPA Fire- 3

NFPA Reactivity- 0

6 - ACCIDENTAL RELEASE MEASURES

PERSONNEL PRECAUTIONS:	Use personal protective equipment.
ENVIRONMENTAL PRECAUTIONS:	Absorb spill with inert material and place in a chemical waste container. Provide ventilation. Clean up spills immediately and observe precautions related to protective equipment.
SPILL CLEANUP MEASURES:	Avoid runoff into ditches, storm sewers and other waterways.

7 - HANDLING AND STORAGE

HANDLING:	Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling.
STORAGE:	Store in a cool dry well ventilated area. Keep away from heat and flame.
HYGIENE:	Avoid or minimize skin contact and inhalation.

8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS:	The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits. Eye washes and showers for emergency use.
EYE / FACE PROTECTION:	Wear splash goggles on face to protect eyes.
SKIN PROTECTION:	Wear butyl rubber gloves, protective clothing and chemical resistant boots.
RESPIRATORY PROTECTION:	If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers.
OTHER PROTECTIONS:	Facilities that store or utilize this material should be equipped with an eyewash facility and a safety shower.
PEL (OSHA) / TLV (ACGIH):	Xylenes (1330-20-7) PEL (OSHA): 100 ppm (TWA) TLV (ACGIH): 100 ppm (TWA), 150 ppm (STEL)

Methyl Ethyl Ketone (78-93-3)	PEL (OSHA): 200 ppm (TWA) TLV (ACGIH): 200 ppm (TWA), 300 ppm (STEL)
Butanol (71-36-3)	PEL (OSHA): 100 ppm (TWA) TLV (ACGIH): 20 ppm (TWA)
Toluene (108-88-3)	PEL (OSHA): 200 ppm (TWA) TLV (ACGIH): 20 ppm (TWA)
Light Aromatic Solvent Naphtha (64742-95-6)	PEL (OSHA): Not Established TLV (ACGIH): Not Established
Acetone (67-64-1)	PEL (OSHA): 750 ppm (TWA), 1000 ppm (STEL) TLV (ACGIH): 500 ppm (TWA), 750 ppm (STEL)
Isopropanol (67-63-0)	PEL (OSHA): 400 ppm (TWA) TLV (ACGIH): 200 ppm (TWA), 400 ppm (STEL)
Methanol (67-56-1)	PEL (OSHA): 200 ppm (TWA) TLV (ACGIH): 200 ppm (TWA), 250 ppm (STEL)
Isobutyl Acetate (110-19-0)	PEL (OSHA): 150 ppm (TWA) TLV (ACGIH): 150 ppm (TWA)
Methyl Isoamyl Ketone (110-12-3)	PEL (OSHA): 100 ppm (TWA) TLV (ACGIH): 50 ppm (TWA)
Ethylbenzene (100-41-4)	PEL (OSHA): 100 ppm (TWA), 125 ppm (STEL) TLV (ACGIH): 100 ppm (TWA)
Formaldehyde (50-00-0)	PEL (OSHA): 0.75 ppm (TWA); 0.5 ppm Action Level; 2 ppm (STEL) TLV (ACGIH): 0.3 ppm Ceiling
Titanium Dioxide (13463-67-7)	PEL (OSHA): 15 mg/m ³ (TWA) TLV (ACGIH): 10 mg/m ³ (TWA)
Diisononyl Phthalate (68515-48-0)	PEL (OSHA): Not Established TLV (ACGIH): Not Established

9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL APPEARANCE:	Opaque Liquid
COLOR:	White
FLASH POINT:	-4 °F
BOILING RANGE:	176 - 293 °F
DENSITY:	8.7 - 9.1 lbs/gal
MATERIAL VOC (as supplied):	4.4 lbs/gal 523 g/l
COATING VOC (EPA Method 24):	4.4 lbs/gal 523 g/l

10 - STABILITY AND REACTIVITY

CHEMICAL STABILITY:	The risk for chemical reactivity is low to none.
HAZARDOUS POLYMERIZATION:	Hazardous polymerization will not occur.
MATERIALS TO AVOID:	None.
DECOMPOSITION PRODUCTS (FIRE):	carbon monoxide; carbon dioxide; aldehydes; formaldehyde; ammonia; oxides of nitrogen

11 - TOXICOLOGICAL INFORMATION

LD ₅₀ , LC ₅₀ :	Xylenes (1330-20-7)
---------------------------------------	---------------------

LD50 (oral rat): 4300 mg/kg
LC50 (inhalation rat): 5000 ppm (4 hr)

Methyl Ethyl Ketone (78-93-3)
LD50 (oral rat): 2737 mg/kg
LC50 (inhalation rat): 23,500 mg/m3 (8 hr)

Butanol (71-36-3)
LD50 (oral rat): 790 mg/kg
LC50 (inhalation rat): 8,000 pm (4 hr)

Toluene (108-88-3)
LD50 (oral rat): 930 mg/kg
LC50 (inhalation rat): 9980 ppm (8 hr)

Light Aromatic Solvent Naphtha (64742-95-6)
LD50 (oral rat): 8,400 mg/kg
LC50 (inhalation rat): > 18,000 ppm

Acetone (67-64-1)
LD50 (oral rat): 5,800 mg/kg
LC50 (inhalation rat): 50,100 mg/m3 (8 hr)

Isopropanol (67-63-0)
LD50 (oral rat): 5,045 mg/kg
LC50 (inhalation rat): 16,000 ppm (8 hr)

Methanol (67-56-1)
LD50 (oral rat): 5,600 mg/kg
LC50 (inhalation rat): 64,000 ppm (4 hr)

Isobutyl Acetate (110-19-0)
LD50 (oral rat): 4,350 mg/kg
LC50 (inhalation rat): 3,500 ppm (4 hr)

Methyl Isoamyl Ketone (110-12-3)
LD50 (oral rat): 5,700 mg/kg
LC50 (inhalation rat): 3,813 ppm (6 hr)

Ethylbenzene (100-41-4)
LD50 (oral rat): 3,500 mg/kg
LC50 (inhalation rat): Not Established

Formaldehyde (50-00-0)
LD50 (oral rat): 800 mg/kg
LC50 (inhalation rat): 1070 mg/m3 (4 hr)

Titanium Dioxide (13463-67-7)
LD50 (oral rat): Not Established
LC50 (inhalation rat): Not Established

Diisononyl Phthalate (68515-48-0)
LD50 (oral rat): Not Established
LC50 (inhalation rat): Not Established

12 - ECOLOGICAL INFORMATION

No data available.

13 - DISPOSAL CONSIDERATIONS

Waste from this product is hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Dispose of waste in accordance with Federal, State and Local regulations regarding pollution.

14 - TRANSPORT INFORMATION

DOT UN Number: UN 1263
DOT Hazard Class: Class 3 : Packing Group II
DOT Description/Name: Paint or Paint Related Material

15 - REGULATORY INFORMATION

TSCA CERTIFICATION: The chemicals in this material are on the TSCA Section 8 Inventory.
SARA 313: This product contains a toxic chemical or chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372:

Xylenes (1330-20-7); Methyl Ethyl Ketone (78-93-3); Butanol (71-36-3); Toluene

(108-88-3); Light Aromatic Solvent Naphtha (64742-95-6); Isopropanol (67-63-0); Methanol (67-56-1); Ethylbenzene (100-41-4); Formaldehyde (50-00-0)

California Proposition 65:

This product contains a toxic chemical or chemicals listed by California as known to cause cancer, birth defects or other reproductive harm in compliance with Proposition 65, the Safe Drinking Water and Toxic Enforcement Act of 1986 (concentration > 0.1% by weight):

Toluene (108-88-3); Ethylbenzene (100-41-4); Formaldehyde (50-00-0)

16 - OTHER INFORMATION

HMIS Key

4 = Severe Hazard
3 = Serious Hazard
2 = Moderate Hazard
1 = Slight Hazard
0 = Minimal Hazard

Acronyms and Abbreviations

ACGIH - American Conference of Governmental Industrial Hygiene (<http://www.acgih.org>)
OSHA - U.S. Occupational Health and Safety Administration (<http://www.osha.gov>)
IARC - International Agency for Research on Cancer (<http://www.iarc.fr>)
NTP - National Toxicology Program (<http://ntp.niehs.nih.gov>)
NIOSH - National Institute for Occupational Safety and Health (<http://www.cdc.gov/niosh>)

PEL - Permissible Exposure Limit
TLV - Threshold Limit Value
TWA - Time Weighted Average (over 8 hour period)
STEL - Short Term Exposure Limit

NFPA is a registered trademark of the National Fire Protection Association (www.nfpa.org).
HMIS is a registered trademark of the National Paint & Coatings Association (www.paint.org/hmis/).

DISCLAIMER

This document is generated to distribute health, safety and environmental data. It is not a specification sheet nor should any data be construed as a specification. The information on this MSDS was obtained from sources which we believe are reliable. The information is provided without any warranty, expressed or implied, regarding its correctness. Some information and conclusions are drawn from sources other than direct tests on the product.

The methods of handling, storage, use and disposal of the product are beyond our control and for this and other reasons we do not assume responsibility. We expressly disclaim liability for loss, damage, or expense arising out of or in any way connected with the handling, storage, use or disposal of this product.

If the product is used as a component in another product, this MSDS information may not be applicable.