



Coatings Technology Since 1899

PRODUCT DATA SHEET

No-Mo Rust Exterior Barn & Roof Rust Inhibitive Enamel One Coat Aluminum

Product Code: 021199

DESCRIPTION

Sampson 021199 No Mo Rust Exterior Barn & Roof Rust Inhibitive Enamel Aluminum is part of our highest quality line of rust preventative coatings. It is a metallic pigmented high performance architectural coating formulated to provide the maximum possible protection to exterior (outdoors) exposed metal from a one coat field-application.

No Mo Rust has rust inhibitors that prevent flash rusting during application and inhibit the process of rusting after the paint has dried. Special water-resistant resins seal out moisture even in the most severe exposures.

It is formulated for maximum adhesion to metal.

FEATURES

- Excellent Adhesion
- Rust Prevention
- Water Resistance
- Maximum Protection

PHYSICAL PROPERTIES

Vehicle Type:	Alkyd
Weight Solids:	52 - 54 %
Volume Solids:	42 - 44 %
Weight Per Gallon:	8 - 8.1 lbs/gal
VOC (lbs/gal):	< 3.9 lbs/gal
VOC (g/l):	< 460 g/l
Flash point:	104 °F
Coverage per gallon ¹ :	350 - 400 ft ² /gal
Dry film thickness:	2 - 3 mils
Dry Time Touch ² :	3 - 4 hours
Reduction Solvent:	022008 Mineral Spirits
Clean Up Solvent:	022008 Mineral Spirits
Application Method:	Spray, brush, roll

1. Coverage per gallon varies with several factors including the painter, force applied and surface porosity; because of this variability, actual coverage may be outside of the estimated range.

2. Dry times may vary due to film thickness, temperature, humidity and air movement.

3. A light sanding is recommended after 48 hours cure to ensure proper intercoat adhesion.

RECOMMENDED PRIMERS

021548 Ceramel Rustproof Primer Gray

Sampson Coatings 1900 Ellen Road Richmond, VA 23230
 1.800.368.2677 804.359.5011 Fax 804.353.3706

SAFETY:

Before starting any of the following procedures, be sure you have and use Personal and Environmental Protective Equipment for all hazards involved. Please read the Material Safety Data Sheet information before using this product.

ADVISORY:

The National Paint and Coatings Association (NPCA) has determined that 80% of all paint and coatings failures can be directly related to improper or inadequate surface preparation.

National Paint and Coatings Association, <http://www.paint.org>

DANGER!
VAPOR HARMFUL!
COMBUSTIBLE LIQUID AND VAPOR;
HARMFUL OR FATAL IF SWALLOWED;

PRECAUTIONS:

Low temperature, high humidity, heavy application and excessive film build will extend drying times.

WARNING:

Use only with adequate ventilation. Do not breathe vapors or spray mists. Ensure fresh air entry during application and drying. If sanding, applying by spray application, or you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor mist levels above applicable limits, wear an appropriate properly fitted respirator (NIOSH approved) during and after application. Follow manufacturer's directions for respirator use. Close container after each use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

If you scrape, sand or remove old paint from any surface, you may release lead dust or other chemical dust hazards. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.

Wear a NIOSH-approved respirator to control dust exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

National Institute for Occupational Safety and Health, <http://www.cdc.gov/niosh/programs/>
Mine Safety and Health Administration, <http://www.msha.gov>

FIRST AID:

If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY. In case of eye contact, flush eyes immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water.

SPILL:

If spilled, contain spilled material and remove with inert absorbent.

DISPOSAL:

Dispose of contaminated absorbent, container, and unused contents in accordance with local, state and federal regulations.

Always consult your Sampson Representative for Special Problem Applications.

The furnishing of the information contained herein does not constitute representation by Sampson Coatings that any product is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of Sampson Coatings or any third party. Sampson Coatings assumes no liability for any infringement which may arise out of the use of this product.

Sampson Coatings warrants that its products meet the specifications which it sets for them. Sampson Coatings **DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION**, expressed or implied, including but not limited to warranties of **MERCHANTABILITY** and **FITNESS** for a particular purpose. Receipt of products from Sampson Coatings constitutes acceptance of the terms of this warranty, contrary provisions of purchase orders not withstanding. In the event that Sampson Coatings finds that the product(s) delivered are out of specification, Sampson Coatings will, at its sole discretion, either replace the product(s) or refund the purchase price thereof, and Sampson Coatings choice of one of these remedies shall be the buyer's (purchasers) sole remedy. Sampson Coatings will under no circumstances be liable for any consequential damages, except in so far as liability mandated by law. Sampson Coatings will deliver products at agreed times in so far as it is reasonably able to do so, but Sampson Coatings shall not be liable for failure to deliver on time when the failure is beyond its reasonable control.